

# Product data sheet

Specifications



## Variable speed drive, ATV312, 1.5kW, 4.2kVA, 61W, 380 to 500V, 3 phase supply, Modbus, CANopen

ATV312HU15N4

! Discontinued on: 26 January 2021

! To be end-of-service on: 01 January 2026

! Discontinued - Service only

### Main

|                                    |   |
|------------------------------------|---|
| Range of product                   | Altivar 312   |
| Product or component type          | Variable speed drive  |
| Product destination                | Asynchronous motors   |
| Product specific application       | Simple machine  |
| Assembly style                     | With heat sink  |
| Component name                     | ATV312  |
| Motor power kW                     | 1.5 kW  |
| Motor power hp                     | 2 hp  |
| [Us] rated supply voltage          | 380...500 V - 15...10 %   |
| Supply frequency                   | 50...60 Hz - 5...5 %  |
| Network number of phases           | 3 phases  |
| Line current                       | 6.4 A at 380 V, I <sub>sc</sub> = 5 kA<br>4.8 A at 500 V  |
| EMC filter                         | Integrated  |
| Apparent power                     | 4.2 kVA   |
| Maximum transient current          | 6.2 A for 60 s  |
| Power dissipation in W             | 61 W at nominal load  |
| Speed range                        | 1...50  |
| Asynchronous motor control profile | Factory set : constant torque<br>Sensorless flux vector control with PWM type motor control signal  |
| Electrical connection              | AI1, AI2, AI3, AOV, AOC, R1A, R1B, R1C, R2A, R2B, LI1...LI6 terminal 2.5 mm <sup>2</sup> AWG 14<br>L1, L2, L3, U, V, W, PA, PB, PA/+, PC/- terminal 5 mm <sup>2</sup> AWG 10  |
| Supply                             | Internal supply for logic inputs: 19...30 V 100 mA, protection type: overload and short-circuit protection<br>Internal supply for reference potentiometer (2.2 to 10 kOhm): 10...10.8 V 10 mA, protection type: overload and short-circuit protection |
| Communication port protocol        | Modbus<br>CANopen   |
| IP degree of protection            | IP20 on upper part without cover plate<br>IP21 on connection terminals<br>IP31 on upper part<br>IP41 on upper part  |
| Option card                        | Communication card for CANopen daisy chain<br>Communication card for DeviceNet<br>Communication card for Fipio  |

## Complementary

|  |  |
|--|--|
| <b>Supply voltage limits</b>               | 323...550 V  |
| <b>Prospective line I<sub>sc</sub></b>     | 5 kA   |
| <b>Continuous output current</b>           | 4.1 A at 4 kHz   |
| <b>Output frequency</b>                    | 0...500 Hz   |
| <b>Nominal switching frequency</b>         | 4 kHz  |
| <b>Switching frequency</b>                 | 2...16 kHz adjustable  |
| <b>Transient overtorque</b>                | 170...200 % of nominal motor torque  |
| <b>Braking torque</b>                      | 150 % during 60 s with braking resistor<br>100 % with braking resistor continuously<br>150 % without braking resistor  |
| <b>Regulation loop</b>                     | Frequency PI regulator   |
| <b>Motor slip compensation</b>             | Suppressable<br>Adjustable<br>Automatic whatever the load  |
| <b>Output voltage</b>                      | <= power supply voltage  |
| <b>Tightening torque</b>                   | AI1, AI2, AI3, AOV, AOC, R1A, R1B, R1C, R2A, R2B, LI1...LI6: 0.6 N.m<br>L1, L2, L3, U, V, W, PA, PB, PA+, PC/-: 1.2 N.m  |
| <b>Insulation</b>                          | Electrical between power and control   |
| <b>Analogue input number</b>               | 3  |
| <b>Analogue input type</b>                 | AI1 configurable voltage 0...10 V, input voltage 30 V max, impedance: 30000 Ohm<br>AI2 configurable voltage +/- 10 V, input voltage 30 V max, impedance: 30000 Ohm<br>AI3 configurable current 0...20 mA, impedance: 250 Ohm   |
| <b>Sampling duration</b>                   | AI1, AI2, AI3: 8 ms analog<br>LI1...LI6: 4 ms discrete   |
| <b>Response time</b>                       | AOV, AOC 8 ms for analog<br>R1A, R1B, R1C, R2A, R2B 8 ms for discrete  |
| <b>Linearity error</b>                     | +/- 0.2 % for output   |
| <b>Analogue output number</b>              | 1  |
| <b>Analogue output type</b>                | AOC configurable current: 0...20 mA, impedance: 800 Ohm, resolution: 8 bits<br>AOV configurable voltage: 0...10 V, impedance: 470 Ohm, resolution: 8 bits  |
| <b>Discrete input logic</b>                | Logic input not wired (LI1...LI4), < 13 V (state 1)<br>Negative logic (source) (LI1...LI6), > 19 V (state 0)<br>Positive logic (source) (LI1...LI6), < 5 V (state 0), > 11 V (state 1)   |
| <b>Discrete output number</b>              | 2  |
| <b>Discrete output type</b>                | Configurable relay logic: (R1A, R1B, R1C) 1 NO + 1 NC - 100000 cycles<br>Configurable relay logic: (R2A, R2B) NC - 100000 cycles   |
| <b>Minimum switching current</b>           | R1-R2 10 mA at 5 V DC  |
| <b>Maximum switching current</b>           | R1-R2: 2 A at 250 V AC inductive load, cos phi = 0.4 and L/R = 7 ms<br>R1-R2: 2 A at 30 V DC inductive load, cos phi = 0.4 and L/R = 7 ms<br>R1-R2: 5 A at 250 V AC resistive load, cos phi = 1 and L/R = 0 ms<br>R1-R2: 5 A at 30 V DC resistive load, cos phi = 1 and L/R = 0 ms   |
| <b>Discrete input number</b>               | 6  |
| <b>Discrete input type</b>                 | (LI1...LI6) programmable at 24 V, 0...100 mA for PLC, impedance: 3500 Ohm  |
| <b>Acceleration and deceleration ramps</b> | S, U or customized<br>Linear adjustable separately from 0.1 to 999.9 s   |
| <b>Braking to standstill</b>               | By DC injection  |
| <b>Protection type</b>                     | Input phase breaks: drive<br>Line supply overvoltage and undervoltage safety circuits: drive<br>Line supply phase loss safety function, for three phases supply: drive<br>Motor phase breaks: drive<br>Overcurrent between output phases and earth (on power up only): drive<br>Overheating protection: drive<br>Short-circuit between motor phases: drive |

Thermal protection: motor

|                              |  |
|------------------------------|--|
| <b>Insulation resistance</b> | >= 500 mOhm 500 V DC for 1 minute  |
| <b>Local signalling</b>      | 1 LED (red) for drive voltage<br>Four 7-segment display units for CANopen bus status       |
| <b>Time constant</b>         | 5 ms for reference change  |
| <b>Frequency resolution</b>  | Analog input: 0.1...100 Hz<br>Display unit: 0.1 Hz   |
| <b>Connector type</b>        | 1 RJ45 for Modbus/CANopen  |
| <b>Physical interface</b>    | RS485 multidrop serial link  |
| <b>Transmission frame</b>    | RTU  |
| <b>Transmission rate</b>     | 10, 20, 50, 125, 250, 500 kbps or 1 Mbps for CANopen<br>4800, 9600 or 19200 bps for Modbus |
| <b>Number of addresses</b>   | 1...127 for CANopen<br>1...247 for Modbus  |
| <b>Number of drive</b>       | 127 for CANopen<br>31 for Modbus   |
| <b>Marking</b>               | CE   |
| <b>Operating position</b>    | Vertical +/- 10 degree   |
| <b>Outer dimension</b>       | 382 x 239 x 170 mm<br>143 x 105 x 150 mm<br>184 x 149 x 157 mm                             |
| <b>Height</b>                | 143 mm   |
| <b>Width</b>                 | 107 mm   |
| <b>Depth</b>                 | 152 mm   |
| <b>Net weight</b>            | 1.8 kg   |

## Environment

|  |   |
|--|---|
| <b>Dielectric strength</b>                   | 2410 V DC between earth and power terminals<br>3400 V AC between control and power terminals  |
| <b>Electromagnetic compatibility</b>         | 1.2/50 $\mu$ s - 8/20 $\mu$ s surge immunity test level 3 conforming to IEC 61000-4-5<br>Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4<br>Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2<br>Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3 |
| <b>Standards</b>                             | IEC 61800-3<br>IEC 61800-5-1  |
| <b>Product certifications</b>                | UL<br>DNV<br>CSA<br>C-Tick<br>NOM<br>GOST   |
| <b>Pollution degree</b>                      | 2   |
| <b>Protective treatment</b>                  | TC  |
| <b>Vibration resistance</b>                  | 1 gn (f= 13...150 Hz) conforming to EN/IEC 60068-2-6<br>1.5 mm (f= 3...13 Hz) conforming to EN/IEC 60068-2-6  |
| <b>Shock resistance</b>                      | 15 gn for 11 ms conforming to EN/IEC 60068-2-27   |
| <b>Relative humidity</b>                     | 5...95 % without condensation conforming to IEC 60068-2-3<br>5...95 % without dripping water conforming to IEC 60068-2-3  |
| <b>Ambient air temperature for storage</b>   | -25...70 °C   |
| <b>Ambient air temperature for operation</b> | -10...50 °C without derating (with protective cover on top of the drive)<br>-10...60 °C with derating factor (without protective cover on top of the drive)   |
| <b>Operating altitude</b>                    | <= 1000 m without derating<br>1000...3000 m with current derating 1 % per 100 m   |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 16.996 cm |
| Package 1 Width              | 17.179 cm |
| Package 1 Length             | 20.62 cm  |
| Package 1 Weight             | 1.972 kg  |
| Unit Type of Package 2       | S06       |
| Number of Units in Package 2 | 27        |
| Package 2 Height             | 73.5 cm   |
| Package 2 Width              | 60.0 cm   |
| Package 2 Length             | 80.0 cm   |
| Package 2 Weight             | 63.0 kg   |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>   |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>  |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End of Life Information</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

## Recommended replacement(s)

ATV312HU15N4 is replaced by:

1x



Variable speed drive, Altivar Machine ATV320, 1.5 kW, 380...500 V, 3 phases, compact  
ATV320U15N4C